

METALLİC SOLVENT GLASS PAINT

-	tion date:	10.05.2015	Version:	
Upgrade date: <u>Issue date:</u>		- 15.08.2016	GBF No:	GBF- LISANS-0036
1. IDE	NTIFICAT		PREPARATION AND	1/6 THE COMPANY/
1.1 Info	rmation at			
Comme	ercial name	: Solvent Glass Paint	Item no: GBF-	LISANS-0036
No	ÜRÜN KO	DU ÜRÜN ADI		
1	30A-21	ALTIN/GOLD		
2	30A-22	SİLVER/GÜMÜŞ		
3	30A-28	BAKIR/KUPFER		
1.2 Con	npany/Man	ufacturer		
Manufacturer: Adress: Telephon: Faks: Web Site:		Lisans Kırtasiye Ofis Gereçleri Şerifali Mah. Emin Sk. No:26 (+90 216 415 45 65 +90 216 420 78 05 www.lisanskirtasiye.com		iye/ İstanbul
Okan 1.4 Em Compa Emerge Nationa	ergency con	as@lisanskirtasiye.com.tr nsultancy ncy call: +90 216 415 45 65 2		



METALLİC SOLVENT GLASS PAINT

Preperation date:	10.05.2015	Version:	1
Upgrade date:	-	GBF No:	GBF- LISANS-0036
Issue date:	15.08.2016	Page:	2 / 6

2. COMPOSITION / INFORMATION ON INGREDIENTS

Item name	Description	% Concentratio n	CAS No	EINEC S No	Classifi cation
Alkyd Resin	Alkyd Resin	40-60	-	-	-
Nitrocellulose damped	Nıtrocellulose damped	8-12	9004-70-0	-	-
Al.Pigment	Al.Pigment	4-5	-	-	-
Liquid Hydrocarbons	Liquid Hydrocarbons	15-25	1330-20-7	-	-
N-Butyl alcohol	N-Butyl alcohol	3-5	71-36-3	-	-
N-Butyl acetate	N-Butyl acetate	4-6	123-86-4		
Acetone	acetone	4-6	67-64-1		

3. HAZARDS IDENTIFICATION

Hazard designation: (1) Substance classified with a health or environmental hazard (2) Substance with a workplace exposure limit

4. FIRST AID MEASURES

After inhalation: Supply fresh air.

After skin contact: Instantly wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for 15 minutes under running water.

Get medical attention if irritation occurs.

After swallowing: Rinse mouth with water and consult doctor. No vomiting

General information: In case of symptoms consult doctor.

5. FIRE-FIGHTING MEASURES

Suitable fire extinguisher: damp fog, extinguishing foam, CO2, extinguishing powder, sand strong jet of water Avoid breathing fire vapours. Fire can creates toxic gases, vapour, fume like carbon monoxide, carbon dioxide, nitrogen oxides.



METALLİC SOLVENT GLASS PAINT

Preperation date:	10.05.2015	Version:	1
Upgrade date:	-	GBF No:	GBF- LISANS-0036
Issue date:	15.08.2016	Page:	3 / 6

6. ACCIDENTAL RELEASE MEASURES

Person-related safety precautions: Measures of environmental protection: bodies.

Avoid skin and eye contact.

Protection: Do not allow product to reach sewage system or water

Measures for cleaning / collection: Absorb with liquid-binding material like sand, universal binders. Disposal of contaminated material in accordance with applicable law

7. HANDLING AND STORAGE

Handling: Ensure good ventilation / exhaustion at the place of work during and after work. Handle the paint with care and under appropriate rules. Do not use near heat and flame. Care for electrostatic discharge.

Storage: Keep glass tightly closed. Keep away from heat, sparks and flame. Care for electrostatic discharge. Store in a cool room with effective ventilation or fresh air. Keep away from food and luxury stimulants.

VCI: Storage class 3A, flammable liquids

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Personal Protection Precaution

Wear suitable protective clothing, protective gloves and protective goggles/mask. Respiratory protection required in insufficiently ventilated working areas and during spraying. An air-fed mask, or for short periods of work, a combination of charcoal filter and particulate filter is recommended.

In case of hypersensitivity of the respiratory tract (e.g. asthmatics and those who suffer from chronic bronchitis) it is inadvisable to work with the product. Symptoms affecting the respiratory tract can also occur several hours after overexposure. Keep away from foodstuffs, drinks and tobacco. Wash hands before breaks and at end of the work. Keep working clothes separate. Take off immediately all contaminated clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 General information Form (Atmosphere temeperature) Liquid Color See Section 1. Odour Smell of solvent

9.2 Important Health, Safety and Environment Information

Density	Approximately 910 kg/m ³ at 20 °C
Viscosity	Approximately 300 Sec in DIN Cup s at 23°C
Solubility in water	not miscible
Flash point	< 21 °C



METALLİC SOLVENT GLASS PAINT

Preperation date:	10.05.2015	Version:	1
Upgrade date:	-	GBF No:	GBF- LISANS-0036
Issue date:	15.08.2016	Page:	4 / 6

Evaporation rate	< 1	
0.2 Additional information		
9.3 Additional information No additional information		

10. STABILITY AND REACTIVITY No decomposition if used according to specifications.
Heating: flammable, flash point + 30 to 39 $^{\circ}$ C
Reactions: oxidative reagents
11. TOXICOLOGICAL INFORMATION
There are no data of the ready preparation available.
LD50° > 2000 mg/kg
° preparation, raw materials
Information from practical use
Eye contact: May cause moderate irritation and paste up eyelids. Paint contains organic solvents, danger of aspiration.
R 36 Irritates eyes
Skin: no irritation *
Eyes: irritation *
* Literature, rabbits
12. ECOLOGICAL INFORMATION
12. ECOLOGICAL INFORMATION
Keep out of soil, water, rivers, lakes and ground-water.
Please observe the local regulations for sewage and water.
13. DISPOSAL INFORMATION
Please note the local regulations for sewage. Dispose of remaining paint in accordance with
applicable
country, federal, state and local regulations. Dispose of packaging according to regulations on the
disposal of packaging. Absolutely cleaned packaging can be recycled.
Suggestion for controlled waste disposal: burning.
EC: EWC-no. depends on way of use, suggestion. EWC-No.: 08 01 11, paint and enamel rubbish containing organic solvents. Or other
harmful ingredients.
namiu ingreuenta.



METALLİC SOLVENT GLASS PAINT

Preperation date:	10.05.2015	Version:	1
Upgrade date:	-	GBF No:	GBF- LISANS-0036
Issue date:	15.08.2016	Page:	5 / 6

14.TRANSPORTATION INFORMATION
Keep cap tightly closed. Keep away from heat, sparks or flame.
Keep away from food and luxury stimulants.
Flammable liquid
Paint related material
Flashpoint: +39°C
ADR: UN 1263
Label 3
Pack. group III
Spez. regul. 640E
No. of danger 30
Sea: UN 1263
IMO-Class 3
EmS No. 3-05; F-E, S-E
Pack. group 3 Air: UN 1263
Class 3
Pack. group III
15. REGULATORY INFORMATION
Xi Irritant
Risk phrases
R 10 Flammable
R 36 Irritates eyes
Safety advises
S 2 Keep away from children
S 7 Keep cap tightly closed
S 16 Keep away from heat, sparks or flame
S 23 Do not inhale vapour & aerosols
S 24/25 Avoid eye and skin contact
S 51 Use only at a well ventilated working place



METALLİC SOLVENT GLASS PAINT

Preperation date:	10.05.2015	Version:	1
Upgrade date:	-	GBF No:	GBF- LISANS-0036
Issue date:	15.08.2016	Page:	6/6

16.OTHER INFORMATION

16.1 Precautions

The paint contains solvents. This is a professional artist material which is not suitable for use by children. Not a toy!

The applicable hygiene and legal regulations have to be observed.

R-phrases from chapter 2..

R 10 Flammable

R 36 Irritates eyes

The information is based upon the present knowledge and experience of our suppliers and manufacturers.

The safety data sheet describes products with regard to their safety requirements. The information does not imply quality assurance.

16.2.1 Contact info

Okan SİVAS osivas@lisanskirtasiye.com.tr Tel: 0216415 45 65- Lisans Kırtasiye Ofis Gereçleri San. ve Tic. A.Ş.

16.3 Issue date 10.05.2015

16.4 Issue no003616.5 Issue and commentsTranslated into Turkish and as directed in regulation 24 December 2008 and no 27092