

# ARTDECO GLASS PAINT ARTDECO CAM BOYASI

 Preperation date:
 10.05.2015
 Version:
 1

 Upgrade date:
 GBF No:
 GBF- LISANS-0034

 Issue date:
 15.08.2016
 Page:
 1 / 6

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY /

## 1.1 Information about item

Commercial name: Artdeco Glass Paint Item no: Lv-Y-030A

No	ÜRÜN KODU	ÜRÜN ADI
1	30A-01	SARI/YELLOW
2	30A-03	TURUNCU/ORANGE
3	30A-04	PEMBE/PİNK
4	30A-06	KIRMIZI/RED
5	30A-08	MOR/VİOLET
6	30A-09	MAVİ/BLUE
7	30A-10	FARBLOS/FARBLOS
8	30A-13	YEŞİL/GREEN
9	30A-14	K.YEŞİL/D.GREEN
10	30A-15	KAHVE/BROWN
11	30A-18	SİYAH/BLACK
12	30A-19	BEYAZ/WHITE
13	30A-30	TURKUAZ/TURKUOİSE

## 1.2 Company/Manufacturer

Manufacturer: Lisans Kırtasiye Ofis Gereçleri San. Ve Tic. A.Ş.

Adress: Şerifali Mah. Emin Sk. No:26 34775 Y.Dudullu/ Ümraniye/ İstanbul

**Telephon:** +90 216 415 45 65 **Faks:** +90 216 420 78 05

Web Site: <a href="www.lisanskirtasiye.com">www.lisanskirtasiye.com</a>

## 1.3 Informer of MSDS

Okan SİVAS osivas@lisanskirtasiye.com.tr

1.4 Emergency consultancy

Company emergency call: +90 216 415 45 65

Emergency call:112

National poison center:114

Fire brigade:110



# ARTDECO GLASS PAINT ARTDECO CAM BOYASI

Preperation date: 10.05.2015 Version: 1

Upgrade date:-GBF No:GBF- LISANS-0034

**Issue date:** 15.08.2016 **Page:** 2 / 6

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

Item name	Description	% Concentratio n	CAS No	EINEC S No	Classifi cation
Alkyd Resin	Alkyd Resin	40-60	-	-	-
Nitrocellulose damped	Nitrocellulose damped	8-12	9004-70-0	-	-
Pigment	Pigment	0,2-0,5	-	-	-
Liquid Hydrocarbons	Liquid Hydrocarbons	15-25	1330-20-7	-	-
N-Butyl alcohol	N-Butyl alcohol	3-5	71-36-3	-	-
N-Butyl acetate	N-Butyl acetate	4-6	123-86-4		
Acetone	acetone	4-6	67-64-1		

#### 3. HAZARDS IDENTIFICATION

*Hazard designation:* (1) Substance classified with a health or environmental hazard (2) Substance with a workplace exposure limit

## 4. FIRST AID MEASURES

After inhalation: Supply fresh air.

After skin contact: Instantly wash with water and soap and rinse thoroughly. After eye contact: Rinse opened eye for 15 minutes under running water.

Get medical attention if irritation occurs.

After swallowing: Rinse mouth with water and consult doctor. No vomiting

General information: In case of symptoms consult doctor.

## 5. FIRE-FIGHTING MEASURES

Suitable fire extinguisher: damp fog, extinguishing foam, CO2, extinguishing powder, sand

Unsuitable fire extinguisher: strong jet of water

Avoid breathing fire vapours. Fire can creates toxic gases, vapour, fume like carbon monoxide,

carbon dioxide, nitrogen oxides.



# ARTDECO GLASS PAINT ARTDECO CAM BOYASI

Preperation date: 10.05.2015 Version: 1

 Upgrade date:
 GBF No:
 GBF- LISANS-0034

 Issue date:
 15.08.2016
 Page:
 3 / 6

#### 6. ACCIDENTAL RELEASE MEASURES

Person-related safety precautions: Avoid skin and eye contact.

Measures of environmental protection: Do not allow product to reach sewage system or water

bodies.

Measures for cleaning / collection: Absorb with liquid-binding material like sand, universal

binders. Disposal of contaminated material in accordance with applicable law

#### 7. HANDLING AND STORAGE

Handling: Ensure good ventilation / exhaustion at the place of work during and after work. Handle the paint with care and under appropriate rules. Do not use near heat and flame. Care for electrostatic discharge.

Storage: Keep glass tightly closed. Keep away from heat, sparks and flame. Care for electrostatic discharge. Store in a cool room with effective ventilation or fresh air. Keep away from food and luxury stimulants.

VCI: Storage class 3A, flammable liquids

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## 8.1 Personal Protection Precaution

Wear suitable protective clothing, protective gloves and protective goggles/mask. Respiratory protection required in insufficiently ventilated working areas and during spraying. An air-fed mask, or for short periods of work, a combination of charcoal filter and particulate filter is recommended.

In case of hypersensitivity of the respiratory tract (e.g. asthmatics and those who suffer from chronic bronchitis) it is inadvisable to work with the product. Symptoms affecting the respiratory tract can also occur several hours after overexposure. Keep away from foodstuffs, drinks and tobacco. Wash hands before breaks and at end of the work. Keep working clothes separate. Take off immediately all contaminated clothing.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 General information

Form (Atmosphere temeperature)	Liquid	
Color	See Section 1.	
Odour	Smell of solvent	

#### 9.2 Important Health, Safety and Environment Information

Density	Approximately 910 kg/m³ at 20 °C	
Viscosity	Approximately 300 Sec in DIN Cup s at	
	23°C	
Solubility in water	not miscible	
Flash point	< 21 °C	



# ARTDECO GLASS PAINT ARTDECO CAM BOYASI

 Preperation date:
 10.05.2015
 Version:
 1

 Upgrade date:
 GBF No:
 GBF- LISANS-0034

 Issue date:
 15.08.2016
 Page:
 4 / 6

Evaporation rate	< 1	
9.3 Additional information		
No additional information		

#### 10. STABILITY AND REACTIVITY

No decomposition if used according to specifications.

Heating: flammable, flash point + 30 to 39 °C

Reactions: oxidative reagents

## 11. TOXICOLOGICAL INFORMATION

There are no data of the ready preparation available.

LD50° > 2000 mg/kg

° preparation, raw materials

## Information from practical use

Eye contact: May cause moderate irritation and paste up eyelids.

Paint contains organic solvents, danger of aspiration.

R 36 Irritates eyes Skin: no irritation \* Eyes: irritation \* \* Literature, rabbits

## 12. ECOLOGICAL INFORMATION

## 12. ECOLOGICAL INFORMATION

Keep out of soil, water, rivers, lakes and ground-water.

Please observe the local regulations for sewage and water.

## 13. DISPOSAL INFORMATION

Please note the local regulations for sewage. Dispose of remaining paint in accordance with applicable

country, federal, state and local regulations. Dispose of packaging according to regulations on the disposal of packaging. Absolutely cleaned packaging can be recycled.

Suggestion for controlled waste disposal: burning.

EC: EWC-no. depends on way of use, suggestion.

EWC-No.: 08 01 11, paint and enamel rubbish containing organic solvents. Or other

· harmful ingredients.



# ARTDECO GLASS PAINT ARTDECO CAM BOYASI

Preperation date:10.05.2015Version:1Upgrade date:-GBF No:GBF- LISANS-0034

**Issue date:** 15.08.2016 **Page:** 5 / 6

## 14.TRANSPORTATION INFORMATION

Keep cap tightly closed. Keep away from heat, sparks or flame.

Keep away from food and luxury stimulants.

Flammable liquid

Paint related material Flashpoint: +39°C

ADR: UN 1263

Label 3

Pack. group III Spez. regul. 640E

No. of danger 30

Sea: UN 1263

IMO-Class 3 Label 3

EmS No. 3-05; F-E, S-E

Pack. group 3

Air: UN 1263

Class 3

Pack. group III

## 15. REGULATORY INFORMATION

Xi Irritant

## Risk phrases

R 10 Flammable

R 36 Irritates eyes

### Safety advises

S 2 Keep away from children

S 7 Keep cap tightly closed

S 16 Keep away from heat, sparks or flame

S 23 Do not inhale vapour & aerosols

S 24/25 Avoid eye and skin contact

S 51 Use only at a well ventilated working place



# ARTDECO GLASS PAINT ARTDECO CAM BOYASI

Preperation date: 10.05.2015 Version: 1

Upgrade date:-GBF No:GBF- LISANS-0034

**Issue date:** 15.08.2016 **Page:** 6 / 6

## **16.OTHER INFORMATION**

#### **16.1 Precautions**

The paint contains solvents. This is a professional artist material which is not suitable for use by children. Not a toy!

The applicable hygiene and legal regulations have to be observed.

R-phrases from chapter 2..

R 10 Flammable

R 36 Irritates eyes

The information is based upon the present knowledge and experience of our suppliers and manufacturers.

The safety data sheet describes products with regard to their safety requirements. The information does not imply quality assurance.

#### 16.2.1 Contact info

Okan SİVAS osivas@lisanskirtasiye.com.tr

Tel: 0216415 45 65- Lisans Kırtasiye Ofis Gereçleri San. ve Tic. A.Ş.

## 16.3 Issue date

10.05.2015

#### 16.4 Issue no

0034

### 16.5 Issue and comments

Translated into Turkish and as directed in regulation 24 December 2008 and no 27092