

SAFETY DATA SHEET

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)



METALURE L-55350

Version 1.0

Revision Date 26.03.2014

Print Date 18.05.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : METALURE L-55350

1.2 Relevant identified uses of the substance or mixture and uses advised against

This information is not available.

1.3 Details of the supplier of the safety data sheet

Company : ECKART GmbH
Guentersthal 4
91235 Hartenstein
Telephone : +499152770
Telefax : +499152777008
E-mail address : msds.eckart@altana.com
Responsible/issuing person

1.4 Emergency telephone number

GBK Gefahrgut Büro GmbH, Ingelheim, Germany:
From outside US: : (001) 352-323-3500
(First call in English, response in your language is possible)
US & Canada (toll free) : 1-800-5355-053

SECTION 2: Hazards identification

GHS Classification

: Flammable liquids, Category 2, H225
Eye irritation, Category 2A, H319
Specific target organ toxicity - single exposure, Category 3,
Central nervous system, H336

GHS-Labeling

SAFETY DATA SHEET

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)





METALURE L-55350

Version 1.0

Revision Date 26.03.2014

Print Date 18.05.2017

- Symbol(s) :  
- Signal word : Danger
- Hazard statements : H225: Highly flammable liquid and vapour.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
- Precautionary statements : **Prevention:**
P210 Keep away from heat/sparks/open flames/hot surfaces.
- No smoking.
P261 Avoid breathing vapours.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER or doctor/ physician if you feel unwell.
P370 + P378 In case of fire: Use for extinction: Dry sand.
Storage:
P403 + P235 Store in a well-ventilated place. Keep cool.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label

Identification	CAS-No.
ethyl acetate	141-78-6
acetone	67-64-1

SAFETY DATA SHEET

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)



METALURE L-55350

Version 1.0

Revision Date 26.03.2014

Print Date 18.05.2017

SECTION 3: Composition/information on ingredients

Hazardous components

Chemical Name	CAS-No. EINECS-No.	Classification and labelling	Concentration[%]
ethyl acetate	141-78-6 205-500-4	Flam. Liq.;2;H225 Eye Irrit.;2A;H319 STOT SE;3;H336	60 - 100
aluminium	7429-90-5 231-072-3	Flam. Sol.;1;H228	10 - 30
acetone	67-64-1 200-662-2	Flam. Liq.;2;H225 Eye Irrit.;2A;H319 STOT SE;3;H336	1 - 5

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
- Move the victim to fresh air.
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water.

SAFETY DATA SHEET

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)



METALURE L-55350

Version 1.0

Revision Date 26.03.2014

Print Date 18.05.2017

If on clothes, remove clothes.

Wash off immediately with soap and plenty of water.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

Immediately flush eye(s) with plenty of water.

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No information available.

Risks : No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Dry sand, Special powder against metal fire

Unsuitable extinguishing media : ABC powder, Carbon dioxide (CO₂), Water, Foam

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

METALURE L-55350

Version 1.0

Revision Date 26.03.2014

Print Date 18.05.2017

5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self contained breathing apparatus for fire fighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

- Personal precautions : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Evacuate personnel to safe areas.

6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

METALURE L-55350

Version 1.0

Revision Date 26.03.2014

Print Date 18.05.2017

Do not flush with water.

Use mechanical handling equipment.
Soak up with inert absorbent material (e.g. sand, silica gel,
acid binder, universal binder, sawdust).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapours/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety

SAFETY DATA SHEET

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)



METALURE L-55350

Version 1.0

Revision Date 26.03.2014

Print Date 18.05.2017

standards.

Earthing of containers and apparatuses is essential. Reaction with water liberates extremely flammable gas (hydrogen) Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep container closed when not in use.

Further information on storage conditions : Protect from humidity and water.

Advice on common storage : Do not store near acids. Do not store together with oxidizing and self-igniting products. Keep away from oxidising agents and strongly acid or alkaline materials. Never allow product to get in contact with water during storage. Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Germany:

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Update	Basis
ethyl acetate	141-78-6	AGW	400 ppm 1 500 mg/m3	2006-01-01	DE TRGS 900

SAFETY DATA SHEET

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)



METALURE L-55350

Version 1.0

Revision Date 26.03.2014

Print Date 18.05.2017

Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
aluminium	7429-90-5	AGW (Inhalable fraction)	10 mg/m ³	2009-02-16	DE TRGS 900
Further information		Commission for dangerous substances			
aluminium	7429-90-5	AGW (Alveolate fraction)	1,35 mg/m ³	2009-02-16	DE TRGS 900
Further information		Commission for dangerous substances			
acetone	67-64-1	TWA	500 ppm 1 210 mg/m ³	2000-06-16	2000/39/EC
Further information		Indicative			
acetone	67-64-1	AGW	500 ppm 1 200 mg/m ³	2010-08-04	DE TRGS 900
Further information		Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).European Union (The EU has established a limit value: deviations in value and peak limit are possible)			

8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Wear face-shield and protective suit for abnormal processing problems.

: Goggles

Hand protection

Material : Solvent-resistant gloves (butyl-rubber)

SAFETY DATA SHEET

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)



METALURE L-55350

Version 1.0

Revision Date 26.03.2014

Print Date 18.05.2017

- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
The exact break through time can be obtained from the protective glove producer and this has to be observed.
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Recommended preventive skin protection
Skin should be washed after contact.
The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- : Use suitable breathing protection if workplace concentration requires.

Environmental exposure controls

- General advice : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)



METALURE L-55350

Version 1.0

Revision Date 26.03.2014

Print Date 18.05.2017

Water

:

:

: The product should not be allowed to enter drains, water courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: silver
Odour	: characteristic
pH	: no data available
Freezing point	: no data available
Boiling point/boiling range	: 76 °C
Flash point	: -4 °C
Bulk density	: no data available
Flammability (solid, gas)	: no data available
Auto-flammability	: no data available
Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Density	: 1,08 g/cm ³
Water solubility	: no data available
Miscibility with water	: immiscible
Solubility in other solvents	: no data available

SAFETY DATA SHEET

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)



METALURE L-55350

Version 1.0

Revision Date 26.03.2014

Print Date 18.05.2017

Partition coefficient: n-octanol/water : no data available
Auto-ignition temperature : no data available
Thermal decomposition : no data available
Viscosity, dynamic : no data available
Viscosity, kinematic : no data available
Flow time : no data available

9.2 Other information

no data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Contact with acids and alkalis may release hydrogen.

Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

Do not allow evaporation to dryness.

10.5 Incompatible materials

Materials to avoid : Acids
Bases

SAFETY DATA SHEET

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)



METALURE L-55350

Version 1.0

Revision Date 26.03.2014

Print Date 18.05.2017

Oxidizing agents

10.6 Hazardous decomposition products

Other information : no data available

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

no data available

Skin corrosion/irritation

Product

May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Product

May cause irreversible eye damage.

Respiratory or skin sensitisation

no data available

Carcinogenicity

no data available

Toxicity to reproduction/fertility

no data available

SAFETY DATA SHEET

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)



METALURE L-55350

Version 1.0

Revision Date 26.03.2014

Print Date 18.05.2017

Reprod.Tox./Development/Teratogenicity

no data available

STOT - single exposure

no data available

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

Further information

Product

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12: Ecological information

12.1 Toxicity

no data available

12.2 Persistence and degradability

no data available

12.3 Bioaccumulative potential

SAFETY DATA SHEET

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)



METALURE L-55350

Version 1.0

Revision Date 26.03.2014

Print Date 18.05.2017

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

no data available

12.6 Other adverse effects

Product:

Additional ecological information : no data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SAFETY DATA SHEET

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)



METALURE L-55350

Version 1.0

Revision Date 26.03.2014

Print Date 18.05.2017

SECTION 14: Transport information

14.1 UN number

ADR : 1263
CN_DG : 1263
TDG : 1263
CFR : 1263
IMDG : 1263
IATA : 1263

14.2 Proper shipping name

ADR : PAINT
CN_DG : PAINT
TDG : PAINT
CFR : PAINT
IMDG : PAINT
IATA : PAINT

14.3 Transport hazard class

ADR : 3
CN_DG : 3
TDG : 3
CFR : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR
Packaging group : III

SAFETY DATA SHEET

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)



METALURE L-55350

Version 1.0

Revision Date 26.03.2014

Print Date 18.05.2017

Classification Code : F1
Hazard identification No : 33
Labels : 3
Tunnel restriction code : (D/E)

CN_DG

Packaging group : III
Labels : 3

TDG

Packaging group : III
Labels : 3

CFR

Packaging group : III
Labels : 3

IMDG

Packaging group : III
Labels : 3
EmS Number : F-E, S-E

IATA

Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packaging group : III
Labels : 3

14.5 Environmental hazards

SAFETY DATA SHEET

Globally Harmonized System of Classification and Labelling of Chemicals (GHS)



METALURE L-55350

Version 1.0

Revision Date 26.03.2014

Print Date 18.05.2017

14.6 Special precautions for user

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

no data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2 Chemical Safety Assessment

no data available

SECTION 16: Other information

Full text of H-Statements

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H228	Flammable solid.
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SAFETY DATA SHEET

Globally Harmonized System of Classification and Labelling of
Chemicals (GHS)



METALURE L-55350

Version 1.0

Revision Date 26.03.2014

Print Date 18.05.2017
